

GOLDSTONE®

金石聲



JIEYANG GOLDSTONE AUDIO EQUIPMENT CO.,LTD

- A: Block B3, Industrial garden, Jiedong economic development trial area, Jieyang, Guangdong 522100, P.R.C.
- T: 86-663-3267799 F: 86-663-3267797
- E: gst@goldstone.cn goldstone2008@gmail.com
- W: www.goldstone.cn What's App: 86-13413967570





GS-6974 35W RMS.
6\"X9\"(16x24cm) 3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 45-22 kHz
Sensitivity: 91 dB/W/m
Magnet: 20 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-6074 25W RMS.
6\" (16cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 55-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 10 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-5074 20W RMS.
5\" (13cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 88 dB/W/m
Magnet: 8 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-4074 15W RMS.
4\" (10cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 80-22 kHz
Sensitivity: 87 dB/W/m
Magnet: 5.5 Oz
Voice coil: 20 mm
Impedance: 4 ohm



GS-6976 35W RMS.
6\"X9\"(16x24cm) 5-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 45-22 kHz
Sensitivity: 91 dB/W/m
Magnet: 20 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-6076 25W RMS.
6\" (16cm)4-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 55-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 10 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-5076 20W RMS.
5\" (13cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 88 dB/W/m
Magnet: 8 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-4076 15W RMS.
4\" (10cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 80-22 kHz
Sensitivity: 87 dB/W/m
Magnet: 5.5 Oz
Voice coil: 20 mm
Impedance: 4 ohm



GS-6978 35W RMS.
6\"X9\"(16x24cm) 3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 45-22 kHz
Sensitivity: 91 dB/W/m
Magnet: 20 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-6078 25W RMS.
6\" (16cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 55-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 10 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-5078 20W RMS.
5\" (13cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 88 dB/W/m
Magnet: 8 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-4078 15W RMS.
4\" (10cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 80-22 kHz
Sensitivity: 87 dB/W/m
Magnet: 5.5 Oz
Voice coil: 20 mm
Impedance: 4 ohm

GOLDSTONE®
金石聲



GS-6096 25W RMS.

6" (16cm)4-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 55-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 10 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-5096 20W RMS.

5" (13cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 88 dB/W/m
Magnet: 8 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-4096 15W RMS.

4" (10cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 80-22 kHz
Sensitivity: 87 dB/W/m
Magnet: 5.5 Oz
Voice coil: 20 mm
Impedance: 4 ohm

GS-6995 35W RMS.

6"X9"(16x24cm) 5-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 45-22 kHz
Sensitivity: 91 dB/W/m
Magnet: 20 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-6095 25W RMS.

6" (16cm)4-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 55-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 10 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-5095 20W RMS.

5" (13cm) 4-way coaxial speaker
Injection cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 88 dB/W/m
Magnet: 8 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-4095 15W RMS.

4"(10cm) 4-way coaxial speaker
Injection cone with rubber edge
Frequency Response: 80-22 kHz
Sensitivity: 87 dB/W/m
Magnet: 5.5 Oz
Voice coil: 20 mm
Impedance: 4 ohm

GS-6948 35W RMS.

6"X9"(16x24cm) 5-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 45-22 kHz
Sensitivity: 91 dB/W/m
Magnet: 20 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-6048 25W RMS.

6"(16cm) 3-way coaxial speaker
Injection cone with rubber edge
Frequency Response: 55-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 10 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-5048 20W RMS.

5"(13cm) 2-way coaxial speaker
Injection cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 88 dB/W/m
Magnet: 8 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-4048 15W RMS.

4"(10cm) 3-way coaxial speaker
Injection cone with rubber edge
Frequency Response: 80-22 kHz
Sensitivity: 87 dB/W/m
Magnet: 5.5 Oz
Voice coil: 20 mm
Impedance: 4 ohm



GS-6995G 40W RMS.

6"x9"(16x24cm)5-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:45-22K Hz
Sensitivity: 93 dB (±2dB)
Magnet: 20 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-6095G 30 W RMS.

6"(16cm)4-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:50-20K Hz
Sensitivity: 89 dB (±2dB)
Magnet: 10 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-5095G 25W RMS.

5"(13cm)4-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:65-22K Hz
Sensitivity: 88 dB (±2dB)
Magnet: 8 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-4095G 20W RMS.

4"(10cm)4-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:80-22K Hz
Sensitivity: 87 dB (±2dB)
Magnet: 5.5 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-4645 25 W RMS.

4"X6"2-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:65-20K Hz
Sensitivity: 90 dB (±2dB)
Magnet: 8 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-6545 30 W RMS.

6.5"(17cm)2-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:50-20K Hz
Sensitivity: 89 dB (±2dB)
Magnet: 10 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-5045 25W RMS.

5"(13cm)2-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:65-22K Hz
Sensitivity: 88 dB (±2dB)
Magnet: 8 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-4045 20W RMS.

4"(10cm)2-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:80-22K Hz
Sensitivity: 87 dB (±2dB)
Magnet: 5.5 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-H1650 45W RMS.

6.5"(17cm)2-Way Coaxial speaker
Paper cone with rubber edge
Freq.Res.:50-20K Hz
Sensitivity: 92 dB (±2dB)
Magnet: 12 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-H1300 35W RMS.

5"(13cm)2-Way Coaxial speaker
Paper cone with rubber edge
Freq.Res.:65-22K Hz
Sensitivity: 91 dB (±2dB)
Magnet: 10 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-H1000 30W RMS.

4"(10cm)2-Way Coaxial speaker
Paper cone with rubber edge
Freq.Res.:80-22K Hz
Sensitivity: 90 dB (±2dB)
Magnet: 6.5 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-SUB6 25W RMS.

6.5"(17cm) Midrange speaker
Titanium cone with rubber edge
Freq.Res.:55-22K Hz
Sensitivity: 90 dB (±2dB)
Magnet: 10 Oz
Voice Coil: 25mm
Impedance:4 ohms



GS-SUB5 20W RMS.

5"(13cm) Midrange speaker
Titanium cone with rubber edge
Freq.Res.:60-22K Hz
Sensitivity: 89 dB (±2dB)
Magnet:8 Oz
Voice Coil: 25mm
Impedance:4 ohms



GS-SUB4 15W RMS.

4"(10cm) Midrange speaker
Titanium cone with rubber edge
Freq.Res.:65-22K Hz
Sensitivity: 88 dB (±2dB)
Magnet:5.4 Oz
Voice Coil: 20mm
Impedance:4 ohms



GS-M1650 45W RMS.

6.5"(17cm) Midrange speaker
IMPP cone with rubber edge
Freq.Res.:50-20K Hz
Sensitivity: 92 dB (±2dB)
Magnet: 12 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-M1300 35W RMS.

5"(13cm) Midrange speaker
IMPP cone with rubber edge
Freq.Res.:65-22K Hz
Sensitivity: 91 dB (±2dB)
Magnet: 10 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS-M1000 30W RMS.

4"(10cm) Midrange speaker
IMPP with rubber edge
Freq.Res.:80-22K Hz
Sensitivity: 90 dB (±2dB)
Magnet: 6.5 Oz Y30
Voice Coil: 25mm Kapton
Impedance:4 ohms



GS10-43 150 W RMS.

10" Subwoofer
Eletro-plating IMPP cone
Freq.Res.:35-2500 K Hz
Sensitivity: 89 dB (±2dB)
Magnet: 40 Oz
DVC: 50mm Kapton
Impedance:4 ohms



GS12-43 180 W RMS.

12" Subwoofer
Eletro-plating IMPP cone
Freq.Res.:30-2000 K Hz
Sensitivity: 90 dB (±2dB)
Magnet: 40 Oz
DVC: 50mm Kapton
Impedance:4 ohms

GS10-45 150 W RMS.

10" Subwoofer
Eletro-plating IMPP cone
Freq.Res.:35-2500 K Hz
Sensitivity: 89 dB (±2dB)
Magnet: 40 Oz
DVC: 50mm Kapton
Impedance:4 ohms

GS12-45 180 W RMS.

12" Subwoofer
Eletro-plating IMPP cone
Freq.Res.:30-2000 K Hz
Sensitivity: 90 dB (±2dB)
Magnet: 40 Oz
DVC: 50mm Kapton
Impedance:4 ohms



GS-C1610 35W RMS.

6.5" (17cm)Component kit speaker
Titanium cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 12 Oz Y30
Voice coil: 25 mm KSV
Impedance: 4 ohm
25mm Silk tweeter
NdFeB magnet
Network unit: 3.5k Hz 12 dB/oct



GS-C1610 40W RMS.

6.5" (17cm)Component kit speaker
IMPP cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 12 Oz Y30
Voice coil: 25 mm KSV
Impedance: 4 ohm
25mm Titanium tweeter
NdFeB magnet
Network unit: 3.5k Hz 12 dB/oct



GS-1620 25W RMS.

6"(16cm)2-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:55-22K Hz
Sensitivity: 89 dB (±2dB)
Magnet: 10 Oz
Voice Coil: 25mm
Impedance:4 ohms



GS-1320 20W RMS.

5"(13cm)2-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:65-22K Hz
Sensitivity: 88 dB (±2dB)
Magnet:8 Oz
Voice Coil: 25mm
Impedance:4 ohms



GS-1020 15W RMS.

4"(10cm)2-Way Coaxial speaker
Injection cone with rubber edge
Freq.Res.:80-22K Hz
Sensitivity: 87 dB (±2dB)
Magnet:5.4 Oz
Voice Coil: 20mm
Impedance:4 ohms



GS-6977 35W RMS.

6"X9"(16x24cm) 4-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 45-22 kHz
Sensitivity: 91 dB/W/m
Magnet: 20 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-6077 25W RMS.

6" (16cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 55-22 kHz
Sensitivity: 89 dB/W/m
Magnet: 10 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-5077 20W RMS.

5" (13cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 65-22 kHz
Sensitivity: 88 dB/W/m
Magnet: 8 Oz
Voice coil: 25 mm
Impedance: 4 ohm



GS-4077 15W RMS.

4" (10cm)3-Way Coaxial Speaker
Injection cone with rubber edge
Frequency Response: 80-22 kHz
Sensitivity: 87 dB/W/m
Magnet: 5.5 Oz
Voice coil: 20 mm
Impedance: 4 ohm



GS-10 DOME TWEETER

- Super Silk Dome Tweeter
- Flush/Angle/Surface Mounting
- KSV 25mm Voice Coil
- Max. Power: 150 Watts
- Freq.Response: 2k-22k Hz
- Sensitivity: 93dB (±1.5dB)
- Impedance: 4 Ohms



GS-10T DOME TWEETER

- Super Titanium Dome Tweeter
- Flush/Angle/Surface Mounting
- KSV 25mm Voice Coil
- Max. Power: 180 Watts
- Freq.Response: 1k-22k Hz
- Sensitivity: 93dB (±1.5dB)
- Impedance: 4 Ohms



GS-200

- D-max dual cone speaker
- 6"/16cm Paper cone with foam edge
- Flush-mounting&water-proof cover
- ASV 25mm voice coil
- Max.power: 300W
- RMS.power: 20 W
- Impedance:4 ohms



GS-1124

- 6-way Sunvisor tweeter speaker
- 60mm x4 piezo tweeter
- 40mm x2 piezo tweeter
- Sensitivity: 90 dB (±2dB)
- Max.power: 300W
- RMS.power: 15 W
- Impedance:4 ohms